

Package ‘N2H4’

July 21, 2025

Type Package

Title Handling Methods for Naver News Text Crawling

Version 0.8.4

Description Provides some functions to get Korean text sample from news articles in Naver which is popular news portal service <<https://news.naver.com/>> in Korea.

License MIT + file LICENSE

URL <https://forkonlp.github.io/N2H4/>, <https://github.com/forkonlp/N2H4>

BugReports <https://github.com/forkonlp/N2H4/issues>

RoxygenNote 7.2.3

Depends R (>= 3.5.0)

Encoding UTF-8

Suggests testthat, devtools, usethis

Imports rvest, jsonlite, tibble, lifecycle, httr2, magrittr

NeedsCompilation no

Author Chanyub Park [aut, cre] (ORCID:
<<https://orcid.org/0000-0001-6474-2570>>)

Maintainer Chanyub Park <mrchypark@gmail.com>

Repository CRAN

Date/Publication 2024-02-25 16:20:02 UTC

Contents

getAllComment	2
getAllCommentHistory	2
getCategory	3
getComment	3
getCommentHistory	4
getContent	5
getMainCategory	5
getSubCategory	6

Index	7
--------------	----------

getAllComment	<i>Get All Comment</i>
---------------	------------------------

Description

Get all comments from the provided news article url on naver

Usage

```
getAllComment(turl)
```

Arguments

turl	character. News article on 'Naver' such as <https://n.news.naver.com/mnews/article/023/0003712918>. News article url that is not on Naver.com domain will generate an error.
------	--

Details

Works just like getComment, but this function executed in a fashion where it finds and extracts all comments from the given url.

Value

a [tibble][[tibble::tibble-package]

Examples

```
## Not run:
  getAllComment("https://n.news.naver.com/mnews/article/214/0001195110")

## End(Not run)
```

getAllCommentHistory	<i>Get All Comment History</i>
----------------------	--------------------------------

Description

Get All Comment History

Usage

```
getAllCommentHistory(turl, commentNo)
```

Arguments

turl	character. News article on 'Naver' such as <https://n.news.naver.com/mnews/article/001/0009205077?sid>. News article url that is not on Naver.com domain will generate an error.
commentNo	Parent Comment No.

Value

a [tibble][tibble::tibble-package]

Examples

```
## Not run:
  getAllComment("https://n.news.naver.com/mnews/article/214/0001195110?sid=103")

## End(Not run)
```

getCategory	<i>News Category</i>
-------------	----------------------

Description

News Category

Usage

```
getCategory(fresh = FALSE)
```

Arguments

fresh get data from online. Default is FALSE using cached built-in data.

getComment	<i>Get Comment</i>
------------	--------------------

Description

Get naver news comments. if you want to get data only comment, enter command like below.
 getComment(url)\$result\$commentList[[1]]

Usage

```
getComment(turl, count = 10, type = c("df", "list"))
```

Arguments

turl like <https://n.news.naver.com/mnews/article/023/0003712918>.
 count is a number of comments. Default is 10. "all" works to get all comments.
 type type return df or list. Default is df. df return part of data not all.

Value

a [tibble][tibble::tibble-package]

Examples

```
## Not run:
  getComment("https://n.news.naver.com/mnews/article/421/0002484966?sid=100")

## End(Not run)
```

getCommentHistory	<i>Get Comment History</i>
-------------------	----------------------------

Description

Get naver news comments on user histories.

Usage

```
getCommentHistory(turl, commentNo, count = 10, type = c("df", "list"))
```

Arguments

turl	character. News article on 'Naver' such as <https://n.news.naver.com/mnews/article/001/0009205077?sid=100>. News article url that is not on Naver.com domain will generate an error.
commentNo	Parent Comment No.
count	is a number of comments. Default is 10. "all" works to get all comments.
type	type return df or list. Default is df. df return part of data not all.

Value

a [tibble][tibble::tibble-package]

Examples

```
## Not run:
  cno <- getComment("https://n.news.naver.com/mnews/article/421/0002484966?sid=100")
  getCommentHistory("https://n.news.naver.com/mnews/article/421/0002484966?sid=100",
    cno$commentNo[1])

## End(Not run)
```

getContent	<i>Get Content</i>
------------	--------------------

Description

Get naver news content from links.

Usage

```
getContent(  
  turl,  
  col = c("url", "original_url", "section", "datetime", "edittime", "press", "title",  
         "body")  
)
```

Arguments

turl is naver news link.
col is what you want to get from news. Default is all.

Value

a [tibble][tibble::tibble-package]

Examples

```
## Not run:  
  getContent("https://n.news.naver.com/mnews/article/214/0001195110?sid=103")  
  
## End(Not run)
```

getMainCategory	<i>Get News Main Categories</i>
-----------------	---------------------------------

Description

Get naver news main category names and ids recently.

Usage

```
getMainCategory()
```

Value

a [tibble][tibble::tibble-package]

Examples

```
## Not run:  
  getMainCategory()  
  
## End(Not run)
```

getSubCategory	<i>Get News Sub Categories</i>
----------------	--------------------------------

Description

Get naver news sub category names and urls recently.

Usage

```
getSubCategory(sid1 = 100)
```

Arguments

sid1	Main category id in naver news url. Only 1 value is possible. Default is 100 means Politics.
------	--

Value

a [tibble][tibble::tibble-package]

Examples

```
## Not run:  
  getSubCategory(100)  
  getSubCategory(100, FALSE)  
  
## End(Not run)
```

Index

`getAllComment`, 2
`getAllCommentHistory`, 2
`getCategory`, 3
`getComment`, 3
`getCommentHistory`, 4
`getContent`, 5
`getMainCategory`, 5
`getSubCategory`, 6