

# Package ‘jsdtools’

May 8, 2026

**Title** Jensen-Shannon Divergence Estimation, Confidence Intervals, and Distribution Plots

**Version** 0.1.0

**Description** Estimates Jensen-Shannon divergence (JSD) for quantifying distributional differences between two groups on a given variable. Supports both continuous and discrete variables, with tools for point estimation, bootstrap confidence intervals, and visualization of raw group-specific distributions.

**License** GPL (>= 3)

**Encoding** UTF-8

**RoxygenNote** 7.3.3

**Depends** R (>= 4.0.0)

**Imports** graphics, grDevices, stats

**Suggests** survival, testthat (>= 3.0.0)

**Config/testthat/edition** 3

**NeedsCompilation** no

**Author** Yueqin Hu [aut, cre],  
Yiran Zhou [aut],  
Wenjuan Liu [aut]

**Maintainer** Yueqin Hu <yueqinhu@bnu.edu.cn>

**Repository** CRAN

**Date/Publication** 2026-03-30 18:30:02 UTC

## Contents

fixed_range . . . . .	2
jsd . . . . .	2
jsd_ci . . . . .	3
jsd_continuous . . . . .	4
jsd_continuous_ci . . . . .	5
jsd_discrete . . . . .	6
jsd_discrete_ci . . . . .	7

plot_continuous . . . . .	8
plot_discrete . . . . .	9
plot_dist . . . . .	10

<b>Index</b>	<b>11</b>
--------------	-----------

---

fixed_range	<i>Fixed integration range for continuous JSD</i>
-------------	---------------------------------------------------

---

### Description

Fixed integration range for continuous JSD

### Usage

```
fixed_range(x, y, qrangle = c(0.001, 0.999), extend = 3)
```

### Arguments

x	Numeric vector for group 1.
y	Numeric vector for group 2.
qrangle	Quantile range used to determine the main data span.
extend	Extension multiplier based on IQR.

### Value

Named numeric vector with elements 'L' and 'U'.

---

jsd	<i>Estimate Jensen-Shannon divergence</i>
-----	-------------------------------------------

---

### Description

Unified front-end for JSD estimation for continuous and discrete variables.

### Usage

```
jsd(x, y, type = c("auto", "continuous", "discrete"), base = 2, ...)
```

### Arguments

x	First vector.
y	Second vector.
type	One of "auto", "continuous", or "discrete".
base	Logarithm base. Defaults to 2. Use 'exp(1)' for nats.
...	Additional arguments passed to the type-specific estimator.

**Value**

An object of class "jsd\_estimate".

---

jsd\_ci

*Bootstrap confidence interval for Jensen-Shannon divergence*


---

**Description**

Unified front-end for JSD confidence interval estimation for continuous and discrete variables.

**Usage**

```
jsd_ci(
  x,
  y,
  type = c("auto", "continuous", "discrete"),
  B = 1000,
  conf_level = 0.95,
  base = 2,
  seed = NULL,
  ...
)
```

**Arguments**

x	First vector.
y	Second vector.
type	One of "auto", "continuous", or "discrete".
B	Number of bootstrap replicates.
conf_level	Confidence level. Defaults to 0.95.
base	Logarithm base. Defaults to 2. Use 'exp(1)' for nats.
seed	Optional random seed.
...	Additional arguments passed to the type-specific bootstrap estimator.

**Value**

An object of class "jsd\_ci".

jsd\_continuous

*Estimate JSD for continuous variables***Description**

Computes Jensen-Shannon divergence (JSD) between two numeric vectors using kernel density estimation (KDE) and numerical integration.

**Usage**

```
jsd_continuous(
  x,
  y,
  L = NULL,
  U = NULL,
  base = 2,
  bw = "nrd0",
  kernel = "gaussian",
  grid_n = 4096,
  qrange = c(0.001, 0.999),
  extend = 3,
  eps = 1e-12,
  renormalize = TRUE,
  na_rm = TRUE
)
```

**Arguments**

x	Numeric vector for group 1.
y	Numeric vector for group 2.
L	Optional lower integration bound.
U	Optional upper integration bound.
base	Logarithm base. Defaults to 2. Use 'exp(1)' for nats.
bw	Bandwidth passed to [stats::density()].
kernel	Kernel passed to [stats::density()].
grid_n	Number of grid points used for KDE.
qrange	Quantile range used when 'L' and 'U' are not supplied.
extend	Extension multiplier for the automatically chosen range.
eps	Small constant for numerical stability.
renormalize	Logical; renormalize estimated densities over the grid?
na_rm	Logical; remove missing values?

**Value**

An object of class "jsd\_estimate".

---

jsd\_continuous\_ci      *Bootstrap confidence interval for continuous JSD*

---

## Description

Bootstrap confidence interval for continuous JSD

## Usage

```
jsd_continuous_ci(  
  x,  
  y,  
  B = 1000,  
  conf_level = 0.95,  
  L = NULL,  
  U = NULL,  
  base = 2,  
  bw = "nrd0",  
  kernel = "gaussian",  
  grid_n = 4096,  
  qrangle = c(0.001, 0.999),  
  extend = 3,  
  eps = 1e-12,  
  renormalize = TRUE,  
  seed = NULL,  
  na_rm = TRUE,  
  na_rm_failed = TRUE  
)
```

## Arguments

x	Numeric vector for group 1.
y	Numeric vector for group 2.
B	Number of bootstrap replicates.
conf_level	Confidence level. Defaults to 0.95.
L	Optional lower integration bound.
U	Optional upper integration bound.
base	Logarithm base. Defaults to 2. Use 'exp(1)' for nats.
bw	Bandwidth passed to [stats::density()].
kernel	Kernel passed to [stats::density()].
grid_n	Number of grid points used for KDE.
qrangle	Quantile range used when 'L' and 'U' are not supplied.
extend	Extension multiplier for the automatically chosen range.

eps	Small constant for numerical stability.
renormalize	Logical; renormalize estimated densities over the grid?
seed	Optional random seed.
na_rm	Logical; remove missing values?
na_rm_failed	Logical; drop failed bootstrap draws when summarizing?

**Value**

An object of class `"jsd_ci"`.

---

jsd_discrete	<i>Estimate JSD for discrete variables</i>
--------------	--------------------------------------------

---

**Description**

Computes Jensen-Shannon divergence (JSD) between two discrete variables using empirical probability mass functions.

**Usage**

```
jsd_discrete(
  x,
  y,
  support = NULL,
  base = 2,
  eps = 1e-12,
  add_smoothing = FALSE,
  na_rm = TRUE
)
```

**Arguments**

x	Vector for group 1. Can be numeric, factor, character, or logical.
y	Vector for group 2. Can be numeric, factor, character, or logical.
support	Optional support values. If <code>'NULL'</code> , the union of observed values in <code>'x'</code> and <code>'y'</code> is used.
base	Logarithm base. Defaults to 2. Use <code>'exp(1)'</code> for nats.
eps	Small constant for numerical stability.
add_smoothing	Logical; add 1 to each cell count?
na_rm	Logical; remove missing values?

**Value**

An object of class `"jsd_estimate"`.

---

jsd\_discrete\_ci      *Bootstrap confidence interval for discrete JSD*

---

### Description

Bootstrap confidence interval for discrete JSD

### Usage

```
jsd_discrete_ci(  
  x,  
  y,  
  B = 1000,  
  conf_level = 0.95,  
  support = NULL,  
  base = 2,  
  eps = 1e-12,  
  add_smoothing = FALSE,  
  seed = NULL,  
  na_rm = TRUE,  
  na_rm_failed = TRUE  
)
```

### Arguments

x	Vector for group 1.
y	Vector for group 2.
B	Number of bootstrap replicates.
conf_level	Confidence level. Defaults to 0.95.
support	Optional support values.
base	Logarithm base. Defaults to 2. Use 'exp(1)' for nats.
eps	Small constant for numerical stability.
add_smoothing	Logical; add 1 to each cell count?
seed	Optional random seed.
na_rm	Logical; remove missing values?
na_rm_failed	Logical; drop failed bootstrap draws when summarizing?

### Value

An object of class "jsd\_ci".

---

plot\_continuous      *Plot two continuous distributions*

---

## Description

Plot two continuous distributions

## Usage

```
plot_continuous(  
  x,  
  y,  
  group_names = c("Group 1", "Group 2"),  
  bins = 30,  
  style = c("both", "hist", "density"),  
  main = "Two-group raw distributions",  
  xlab = "Value",  
  ylab = "Density",  
  col_x = rgb(0.2, 0.4, 0.8, 0.4),  
  col_y = rgb(0.8, 0.2, 0.2, 0.4),  
  line_col_x = "#2F5FB3",  
  line_col_y = "#CC3333",  
  lwd = 2,  
  na_rm = TRUE,  
  show_jsd = TRUE,  
  jsd_digits = 3  
)
```

## Arguments

x	Numeric vector for group 1.
y	Numeric vector for group 2.
group_names	Group labels.
bins	Approximate number of histogram bins.
style	One of "both", "hist", or "density".
main	Plot title.
xlab	X-axis label.
ylab	Y-axis label.
col_x	Fill color for group 1.
col_y	Fill color for group 2.
line_col_x	Line color for group 1 density.
line_col_y	Line color for group 2 density.
lwd	Line width for density curves.

na_rm	Logical; remove missing values?
show_jsd	Logical; whether to display JSD on the plot.
jsd_digits	Number of digits for displayed JSD.

**Value**

Invisibly returns plotting data.

---

plot_discrete	<i>Plot two discrete distributions with overlap</i>
---------------	-----------------------------------------------------

---

**Description**

Plot two discrete distributions with overlap

**Usage**

```
plot_discrete(
  x,
  y,
  support = NULL,
  group_names = c("Group 1", "Group 2"),
  main = "Two-group discrete distributions",
  xlab = "Value",
  ylab = "Proportion",
  col_x = adjustcolor("#2F5FB3", alpha.f = 0.2),
  col_y = adjustcolor("#CC3333", alpha.f = 0.2),
  overlap_col = adjustcolor("grey55", alpha.f = 0.35),
  line_col_x = "#2F5FB3",
  line_col_y = "#CC3333",
  lwd = 2,
  pch = 16,
  cex_pt = 1.1,
  las = 1,
  bar_width = 0.2,
  show_jsd = TRUE,
  jsd_digits = 3,
  na_rm = TRUE
)
```

**Arguments**

x	Vector for group 1.
y	Vector for group 2.
support	Optional support values.
group_names	Group labels.

main	Plot title.
xlab	X-axis label.
ylab	Y-axis label.
col_x	Color for group 1.
col_y	Color for group 2.
overlap_col	Fill color for overlap bars.
line_col_x	Line color for group 1.
line_col_y	Line color for group 2.
lwd	Line width.
pch	Point character.
cex_pt	Point size.
las	Axis label style for x-axis.
bar_width	Width of overlap bars.
show_jsd	Logical; whether to display JSD on the plot.
jsd_digits	Number of digits for displayed JSD.
na_rm	Logical; remove missing values?

**Value**

Invisibly returns plotting data.

---

plot_dist	<i>Plot two-group distributions</i>
-----------	-------------------------------------

---

**Description**

Unified front-end for plotting continuous or discrete two-group raw distributions.

**Usage**

```
plot_dist(x, y, type = c("auto", "continuous", "discrete"), ...)
```

**Arguments**

x	First vector.
y	Second vector.
type	One of "auto", "continuous", or "discrete".
...	Additional arguments passed to the type-specific plotting function.

**Value**

Invisibly returns plotting data.

# Index

`fixed_range`, [2](#)

`jsd`, [2](#)

`jsd_ci`, [3](#)

`jsd_continuous`, [4](#)

`jsd_continuous_ci`, [5](#)

`jsd_discrete`, [6](#)

`jsd_discrete_ci`, [7](#)

`plot_continuous`, [8](#)

`plot_discrete`, [9](#)

`plot_dist`, [10](#)