

Package ‘kayadata’

July 12, 2024

Type Package

Title Kaya Identity Data for Nations and Regions

Version 1.4.0

Date 2024-07-07

Description Provides data for Kaya identity variables (population, gross domestic product, primary energy consumption, and energy-related CO2 emissions) for the world and for individual nations, and utility functions for looking up data, plotting trends of Kaya variables, and plotting the fuel mix for a given country or region. The Kaya identity (Yoichi Kaya and Keiichi Yokobori, ``Environment, Energy, and Economy: Strategies for Sustainability" (United Nations University Press, 1998) and https://en.wikipedia.org/wiki/Kaya_identity) expresses a nation's or region's greenhouse gas emissions in terms of its population, per-capita Gross Domestic Product, the energy intensity of its economy, and the carbon-intensity of its energy supply.

URL <https://jonathan-g.github.io/kayadata/>,
<https://github.com/jonathan-g/kayadata>,
<https://doi.org/10.5281/zenodo.8144476>

BugReports <https://github.com/jonathan-g/kayadata/issues>

License MIT + file LICENSE

Depends R (>= 3.5), ggplot2 (>= 3.5.1)

Imports magrittr (>= 2.0.3), forcats (>= 1.0.0), dplyr (>= 1.1.4),
tidyr (>= 1.3.1), stringr (>= 1.5.1), scales (>= 1.3.0), purrr
(>= 1.0.2)

Encoding UTF-8

Language en-US

LazyData true

RoxygenNote 7.3.2

Suggests broom (>= 0.5), knitr (>= 1.22), rmarkdown (>= 1.12),
testthat (>= 2.0), vdiff (>= 0.3.1)

VignetteBuilder knitr**NeedsCompilation** no**Author** Jonathan Gilligan [cre, aut] (<<https://orcid.org/0000-0003-1375-6686>>)**Maintainer** Jonathan Gilligan <jonathan.gilligan@vanderbilt.edu>**Repository** CRAN**Date/Publication** 2024-07-12 16:20:02 UTC

Contents

kayadata-package	2
emissions_factors	3
fuel_mix	4
generation_capacity	5
get_fuel_mix	6
get_kaya_data	7
get_top_down_trends	8
get_top_down_values	9
kaya_data	10
kaya_region_list	11
megawatts_per_quad	11
plot_fuel_mix	12
plot_kaya	13
project_top_down	15
regions	16
td_trends	17
td_values	18
Index	19

kayadata-package	<i>kayadata package</i>
------------------	-------------------------

Description

kayadata is a package for working with Kaya identity data for many countries and regions.

The Kaya identity, named for the economist Yoichi Kaya, who introduced it (Kaya, 1998); It decomposes the energy-related carbon dioxide emissions from a nation, region, or the world into the product of four components:

$$F = P \times g \times e \times f,$$

where F is the total emissions, P is the population, g is the per-capita GDP, e is the energy intensity of the economy, and f is the emissions-intensity of the energy supply. (Nakicenovic and Swart, 2000, Ch. 3, p. 105; Raupach *et al.*, 2007)

The data in this packages covers 1960-2019 for population and GDP, and 1965-2019 for energy and fossil-fuel CO2 emissions.

The package uses data on population and GDP from the World Bank, using market exchange rates (MER) for GDP because those data go back to 1960. From 1990 onward, Purchasing-Power-Parity (PPP) GDP figures are available as `G_ppp` but using these would require re-calculating `G`, `g`, `e`, and `ef` in the `kaya_data` data frame.

The package uses data on energy consumption and fossil-fuel CO2 emissions from the [Energy Institute's 2024 Statistical Review of World Energy](#)

License

The `kayadata` package is open source licensed under the MIT License.

Bug reports

- `kayadata` issue tracker (<https://github.com/jonathan-g/kayadata/issues>)

Author(s)

Maintainer: Jonathan Gilligan <jonathan.gilligan@vanderbilt.edu> ([ORCID](#))

References

Kaya, Yoichi and Keiichi Yokobori, *Environment, Energy, and Economy: Strategies for Sustainability* (United Nations University Press, 1998).

Nakicenovic, Nebojsa, and Rob Swart (Eds.), *Special Report on Emissions Scenarios* (Cambridge University Press, 2000). <https://www.ipcc.ch/report/emissions-scenarios/>

Raupach, Michael R., *et al.*, "Global and regional drivers of accelerating CO2 emissions," *PNAS* **104**, 10288–10293 (2007) [doi:10.1073/pnas.0700609104](https://doi.org/10.1073/pnas.0700609104).

See Also

Useful links:

- <https://jonathan-g.github.io/kayadata/>
- <https://github.com/jonathan-g/kayadata>
- [doi:10.5281/zenodo.8144476](https://doi.org/10.5281/zenodo.8144476)
- Report bugs at <https://github.com/jonathan-g/kayadata/issues>

`emissions_factors` *Get emission factors for different energy sources*

Description

Get emission factors for different energy sources

Usage

```
emissions_factors(collapse_renewables = TRUE)
```

Arguments

collapse_renewables

Combine hydroelectricity and other renewables into a single category.

Value

a tibble of values for emissions factors, in million metric tons of carbon dioxide per quad of energy.

See Also[regions](#)**Examples**

```
e_fac <- emissions_factors()
e_fac
```

fuel_mix	<i>Mix of fuels contributing to primary energy supply for many countries and regions</i>
----------	--

Description

A dataset containing the fuel mix of how many quads and what fraction of total primary energy supply comes from coal, gas, oil, nuclear, and renewable sources.

Usage

fuel_mix

Format

A tibble containing 948 rows and 7 variables

region Country or region name**region_code** Three-letter country or region code**geography** Geographic category: "nation", "region", or "world"**year** The year**fuel** The fuel: "Coal", "Natural Gas", "Oil", "Nuclear", "Hydro", and "Renewables"**quads** The number of quads of that fuel consumed in the given country or region and year**frac** The fraction of that country or region's total primary energy consumption from the fuel**Note**

The data for 2022, from the 2023 release of the Energy Institute's Statistical Review, has inconsistencies in the fuel mix for Hong Kong and Sri Lanka: The percentages add up to 98.7% and 102.9%, respectively. The sums of energy in quads are off by -0.095 and +0.095 quads, respectively, from the total energy figure.

Source

<https://www.energyinst.org/statistical-review/resources-and-data-downloads>

See Also

[regions](#), [get_fuel_mix\(\)](#)

generation_capacity *Get power output from generation sources*

Description

Nameplate capacity and capacity factors for different electrical generation technologies. The average power supplied over a year is the nameplate capacity times the capacity factor.

Usage

```
generation_capacity()
```

Details

Data for fossil fuels comes from EIA

Value

a tibble of values for generation sources

fuel Energy source: Coal, Nuclear, Gas, Solar Thermal, Solar Photovoltaic, Onshore Wind, or Offshore Wind

description Text description of the power source

nameplate_capacity Maximum sustained power output, in megawatts

capacity_factor Capacity factor: the fraction of the nameplate capacity that the plant can provide, averaged over a typical year

References

Environmental Protection Agency (2018) "Electric Power Monthly," (October, 2018) <https://www.eia.gov/electricity/monthly/archive/october2018.pdf>, Table 6.7.A.

Pielke, Jr., Roger A., *The Climate Fix* (Basic Books, 2010).

Examples

```
gc <- generation_capacity()
gc
```

`get_fuel_mix`*Get fuel mix for one or more countries or regions*

Description

Get fuel mix for one or more countries or regions

Usage

```
get_fuel_mix(  
  region_name,  
  collapse_renewables = TRUE,  
  quiet = FALSE,  
  region_code = NULL  
)
```

Arguments

`region_name` A character vector with the names of one or more countries or regions to look up

`collapse_renewables` Combine hydroelectricity and other renewables into a single category.

`quiet` Suppress warnings if there is no data for that country or region.

`region_code` Optional three-letter country or region codes to look up instead of the `region_name`

Value

A tibble of fuel mix for the countries or regions specified. That is, the number of quads of each fuel and the fraction of total primary energy coming from that fuel for each country or region:

region The name of the country or region

year The year reported

fuel The name of the fuel

quads The number of quads per year the country or region consumes

frac The fraction of the country's energy that comes from that fuel

Note

In the latest data from the Energy Institute, there are small discrepancies between the sums of energy for each fuel and the totals, in both quads and `frac`, for Hong Kong and Sri Lanka, as described in the documentation for [fuel_mix](#).

See Also

[regions](#), [fuel_mix](#)

Examples

```

get_fuel_mix("United States")
get_fuel_mix("World", collapse_renewables = FALSE)
get_fuel_mix(region_code = "LCN")

```

get_kaya_data	<i>Get Kaya data for one or more countries or regions</i>
---------------	---

Description

Get Kaya data for one or more countries or regions

Usage

```

get_kaya_data(
  region_name,
  gdp = c("MER", "PPP"),
  quiet = FALSE,
  region_code = NULL
)

```

Arguments

region_name	The name of one or more countries or regions to look up
gdp	Use market exchange rates (MER) or purchasing power parity (PPP). Default is MER.
quiet	Suppress warnings if there is no such country or region.
region_code	Optional three-letter country or region codes to look up instead of the region_name

Details

Units for G , g , e , and ef depend on whether the data is requested in MER or PPP dollars: For MER, dollars are constant 2015 U.S. dollars. For PPP, dollars are constant 2017 international dollars.

`_P_` and MER values for GDP and related quantities are available from 1960 onward.

PPP values for GDP and related quantities are only available from 1990 onward.

Energy-related values (`_E_`, `_F_`, and derived quantities) are available from 1965 onward.

Note that emissions (`_F_`, `_f_`, and `_ef_`) are reported as millions of metric tons of carbon dioxide, not carbon.

Value

a tibble of Kaya identity data for the countries or regions specified:

region The name of the country or region

year The year

P Population, in billions

G Gross domestic product, in trillions of constant 2015 U.S. dollars.

E Total primary energy consumption, in quads

F CO2 emissions from fossil fuel consumption, in millions of metric tons

g Per-capita GDP, in thousands of dollars per person.

e Energy intensity of the economy, in quads per trillion dollars.

f Emissions intensity of the energy supply, in million metric tons per quad.

ef Emissions intensity of the economy, in metric tons per million dollars of GDP.

See Also

[regions](#)

Examples

```
get_kaya_data("Brazil")
get_kaya_data("United Kingdom", "PPP")
get_kaya_data(region_name = "United States")
get_kaya_data(region_code = "MYS")
```

get_top_down_trends	<i>Get top-down trends for Kaya variables for one or more countries or regions, using projections from U.S. Energy Information Administration's International Energy Outlook report.</i>
---------------------	--

Description

Get top-down trends for Kaya variables for one or more countries or regions, using projections from U.S. Energy Information Administration's International Energy Outlook report.

Usage

```
get_top_down_trends(region_name, quiet = FALSE, region_code = NULL)
```

Arguments

region_name	The name of one or more countries or regions to look up
quiet	Suppress warnings if there is no data for the specified countries or regions.
region_code	Optional three-letter country or region codes to look up instead of the region_name

Value

a tibble of trends for P , G , E , F , g , e , f , and ef for each country or region in percent per year.

See Also

[regions](#)

Examples

```
get_top_down_trends("Spain")
get_top_down_trends(region_code = "RUS")
```

get_top_down_values	<i>Get top-down projections of Kaya variables for one or more countries or regions</i>
---------------------	--

Description

Get top-down projections of Kaya variables for one or more countries or regions

Usage

```
get_top_down_values(region_name, quiet = FALSE, region_code = NULL)
```

Arguments

region_name	The name of a country or region to look up
quiet	Suppress warnings if there is no data for that country or region.
region_code	Optional three-letter country or region code to look up instead of the region_name

Value

a tibble of values for P , G , E , F , g , e , f , and ef for each country or region:

region The name of the country or region

P Population, in billions

G Gross domestic product, in trillions of constant 2015 U.S. dollars.

E Total primary energy consumption, in quads

F CO2 emissions from fossil fuel consumption, in millions of metric tons

g Per-capita GDP, in thousands of constant 2015 U.S. dollars per person.

e Energy intensity of the economy, in quads per trillion dollars.

f Emissions intensity of the energy supply, in million metric tons per quad.

ef Emissions intensity of the economy, in metric tons per million dollars of GDP.

See Also[regions](#)**Examples**

```
get_top_down_values("New Zealand")
get_top_down_values("OECD")
get_top_down_values(region_code = "PAK")
```

kaya_data

Kaya identity data for many countries and regions

Description

A dataset containing Kaya identity parameters P, G, E, F, g, e, f, and ef for many countries

Usage

```
kaya_data
```

Format

A tibble containing 5292 rows and 14 variables:

region Country or region name

region_code Three-letter country or region code

geography Geographic category: "nation", "region", or "world"

year The year

P Population, in billions

G Gross domestic product, in trillions of constant 2015 U.S. dollars.

E Total primary energy consumption, in quads

F CO2 emissions from fossil fuel consumption, in millions of tons

g Per-capita GDP, in thousands of constant 2015 U.S. dollars per person.

e Energy intensity of the economy, in quads per trillion dollars.

f Emissions intensity of the energy supply, in million metric tons per quad.

ef Emissions intensity of the economy, in metric tons per million dollars of GDP.

G_ppp Gross domestic product adjusted for purchasing power parity, in trillions of constant 2017 international dollars

G_mer Gross domestic product at market-exchange-rate, in trillions of constant 2015 U.S. dollars

Source

<https://data.worldbank.org/indicator/SP.POP.TOTL>, <https://data.worldbank.org/indicator/NY.GDP.MKTP.KD>, and <https://www.energyinst.org/statistical-review/resources-and-data-downloads>

See Also

[regions](#), [get_kaya_data\(\)](#)

kaya_region_list *Get a list of countries in the Kaya data*

Description

Get a list of countries in the Kaya data

Usage

```
kaya_region_list()
```

Value

a vector of country and region names

See Also

[regions](#)

megawatts_per_quad *The number of megawatts it takes to replace a quad.*

Description

The number of megawatts of average power output over a year to produce one quad of energy

Usage

```
megawatts_per_quad()
```

Value

The number of megawatts equivalent to one quad per year.

Examples

```
mwe <- megawatts_per_quad()
mwe
```

plot_fuel_mix	<i>Plot fuel mix</i>
---------------	----------------------

Description

Plot fuel mix

Usage

```
plot_fuel_mix(
  fuel_mix,
  collapse_renewables = TRUE,
  title = NULL,
  colors = NULL,
  font_size = 20
)
```

Arguments

fuel_mix	A tibble with the mixture of fuels for one or more countries or regions: region The name of the country or region fuel The name of the fuel quads The number of quads per year the country or region consumes frac The fraction of the country's energy that comes from that fuel
collapse_renewables	Combine hydroelectricity and other renewables into a single category.
title	Include a title on the plot. If title is NULL (default) or TRUE, a default title is created from the names of the regions in fuel_mix. If title is a character string, that string is used. If title is FALSE, the plot is produced with no title.
colors	A named vector with the colors to use for Coal, Oil, Natural Gas, Nuclear, Hydro, and Renewables.
font_size	The base font size.

Value

A plot object.

Examples

```
usa_fuel <- get_fuel_mix("United States", collapse_renewables = FALSE)
plot_fuel_mix(usa_fuel)
plot_fuel_mix(usa_fuel, collapse_renewables = FALSE)
plot_fuel_mix(usa_fuel, collapse_renewables = FALSE,
  colors = c(Coal = "black", "Natural Gas" = "gray60",
    Oil = "gray30", Nuclear = "forestgreen",
    Hydro = "royalblue", Renewables="palegreen"))
```

```
plot_fuel_mix("United States")
plot_fuel_mix("USA")
```

plot_kaya	<i>Plot Kaya-identity variable</i>
-----------	------------------------------------

Description

Plot Kaya-identity variable

Usage

```
plot_kaya(
  data,
  variable,
  start_year = NA,
  stop_year = NA,
  y_lab = NULL,
  log_scale = FALSE,
  trend_line = FALSE,
  points = TRUE,
  font_size = 20,
  colors = NULL,
  pre_color = NULL,
  post_color = NULL,
  in_range_color = NULL,
  trend_color = NULL,
  line_sizes = NULL,
  pre_line_size = NULL,
  post_line_size = NULL,
  in_range_line_size = NULL,
  trend_line_size = NULL,
  point_sizes = NULL,
  pre_point_size = NULL,
  post_point_size = NULL,
  in_range_point_size = NULL
)
```

Arguments

data	A tibble with Kaya-identity data or the name of a region or a region code.
variable	The name of the variable to plot (character)
start_year	The year to start highlighting the data (should correspond to the beginning of the trend calculation). Set to NULL to turn off highlighting.
stop_year	The year to stop highlighting the data (should correspond to the beginning of the trend calculation). Set to NULL to turn off highlighting.

<code>y_lab</code>	Optional label for the y-axis
<code>log_scale</code>	Use log scale for y axis
<code>trend_line</code>	Include a trend line
<code>points</code>	Plot points in addition to the line.
<code>font_size</code>	Base size of the font for axis labels and titles.
<code>colors</code>	Named vector of colors to use for the plot. Elements should include PRE, POST, IN-RANGE, and TREND, which respectively give the colors for the portion of the plot before <code>start_year</code> , after <code>stop_year</code> , between <code>start_year</code> and <code>stop_year</code> , and the trend line.
<code>pre_color</code>	Override default color for the portion of the chart before <code>start_year</code> .
<code>post_color</code>	Override default color for the portion of the chart after <code>stop_year</code> .
<code>in_range_color</code>	Override default color for the portion of the chart between <code>start_year</code> and <code>stop_year</code> .
<code>trend_color</code>	Override default color for the trend line.
<code>line_sizes</code>	Named vector of sizes to use for the lines in the plot. Elements should include PRE, POST, IN-RANGE, and TREND, which respectively give the sizes for lines in the portion of the plot before <code>start_year</code> , after <code>stop_year</code> , between <code>start_year</code> and <code>stop_year</code> , and the trend line.
<code>pre_line_size</code>	Override default line size for the portion of the chart before <code>start_year</code> .
<code>post_line_size</code>	Override default line size for the portion of the chart after <code>stop_year</code> .
<code>in_range_line_size</code>	Override default line size for the portion of the chart between <code>start_year</code> and <code>stop_year</code> .
<code>trend_line_size</code>	Override default size for the trend line.
<code>point_sizes</code>	Named vector of sizes to use for the points in the plot. Elements should include PRE, POST, and IN-RANGE, which respectively give the sizes for points in the portion of the plot before <code>start_year</code> , after <code>stop_year</code> , and between <code>start_year</code> and <code>stop_year</code> .
<code>pre_point_size</code>	Override default point size for the portion of the chart before <code>start_year</code> .
<code>post_point_size</code>	Override default point size for the portion of the chart after <code>stop_year</code> .
<code>in_range_point_size</code>	Override default point size for the portion of the chart between <code>start_year</code> and <code>stop_year</code> .

Value

A plot object.

Examples

```

china <- get_kaya_data("China")
plot_kaya(china, "F", 2001, 2011)
## Not run:
uk <- get_kaya_data("United Kingdom")
plot_kaya(uk, "e", log_scale = TRUE, trend_line = TRUE)
plot_kaya(uk, "e", log_scale = TRUE, trend_line = TRUE,
          start_year = 1970, stop_year = 2000,
          colors = c(PRE="limegreen", POST="darkgreen",
                    "IN-RANGE" = "cadetblue", TREND="orange"),
          line_sizes = c(PRE=0.5, POST=0.5, "IN-RANGE"]=1, TREND=1.5),
          point_sizes = c(PRE=2, POST=2, "IN-RANGE"]=3))
plot_kaya(uk, "e", log_scale = TRUE, trend_line = TRUE,
          start_year = 1970, stop_year = 2000,
          pre_color = "limegreen", post_color = "limegreen",
          trend_color = "magenta",
          pre_line_size = 0.5, post_line_size = 0.5,
          trend_line_size = 1.5,
          pre_point_size = 2, post_point_size = 2, in_range_point_size = 3)
plot_kaya("United Kingdom")
plot_kaya("GBR")

## End(Not run)

world <- get_kaya_data("World")
plot_kaya(world, "g", 1982, log_scale = TRUE, trend_line = TRUE)

```

project_top_down	<i>Get top-down projections of Kaya variables for one or more countries or regions for a given year</i>
------------------	---

Description

Get top-down projections of Kaya variables for one or more countries or regions for a given year

Usage

```
project_top_down(region_name, year, quiet = FALSE, region_code = NULL)
```

Arguments

region_name	The name of a country or region to look up
year	The year to project to
quiet	Suppress warnings if there is no data for that country or region.
region_code	Optional three-letter country or region code to look up instead of the region_name

Value

a tibble of values for P , G , E , F , g , e , f , and ef for each country or region:

region The name of the country or region

year The year

P Population, in billions

G Gross domestic product, in trillions of constant 2015 U.S. dollars.

E Total primary energy consumption, in quads

F CO2 emissions from fossil fuel consumption, in millions of metric tons

g Per-capita GDP, in thousands of constant 2015 U.S. dollars per person.

e Energy intensity of the economy, in quads per trillion dollars.

f Emissions intensity of the energy supply, in million metric tons per quad.

ef Emissions intensity of the economy, in metric tons per million dollars of GDP.

See Also

[regions](#)

Examples

```
project_top_down("China", 2037)
project_top_down(region_code = "CHE", year = 2043)
```

regions

Aggregate regional data

Description

Problems with aggregate regional data

Details

The World Bank is missing GDP data for a number of nations, such as Syria and Taiwan. Because of this and the incommensurability between the regions used for aggregate statistics in the World Bank and Energy Institute data, aggregate regional data (e.g., for the Middle East and Africa) should be treated with caution. This problem does not hold for individual nations, where missing data appears as NA values.

td_trends	<i>Top-down projections of trends in Kaya variables for many countries and regions</i>
-----------	--

Description

A dataset containing top-down projections of trends in P, G, and E, from the EIA's International Energy Outlook 2017.

Usage

td_trends

Format

A tibble containing 226 rows and 11 variables

region Country or region name

region_code Three-letter country or region code

geography Geographic category: "nation", "region", or "world"

P Trend in population, in fraction per year

G Trend in gross domestic product, in fraction per year

E Trend in total primary energy consumption, in fraction per year

F Trend in CO2 emissions, in fraction per year

g Trend in per-capita GDP, in fraction per year

e Trend in energy intensity of the economy, in fraction per year

f Trend in emissions intensity of the energy supply, in fraction per year

ef Trend in emissions intensity of the economy, in fraction per year

Source

<https://www.eia.gov/outlooks/archive/ieo17/>

See Also

[regions](#), [get_top_down_trends\(\)](#)

td_values	<i>Top-down projections of future Kaya variables for many countries and regions</i>
-----------	---

Description

A dataset containing top-down projections of P, G, and E, from the EIA's International Energy Outlook 2017.

Usage

td_values

Format

A tibble containing 640 rows and 12 variables

region Country or region name

region_code Three-letter country or region code

geography Geographic category: "nation", "region", or "world"

year The year

P Population, in billions

G Gross domestic product, in trillions of constant 2015 U.S. dollars

E Total primary energy consumption, in quads

F Total CO2 emissions, in millions of metric tons

g Per-capita GDP, in thousands of constant 2015 U.S. dollars per person.

e Energy intensity of the economy, in quads per trillion dollars.

f Emissions intensity of the energy supply, in million metric tons per quad.

ef Emissions intensity of the economy, in metric tons per million dollars of GDP.

Source

<https://www.eia.gov/outlooks/archive/ieo17/>

See Also

[regions](#), [get_top_down_values\(\)](#)

Index

* datasets

- fuel_mix, 4
- kaya_data, 10
- td_trends, 17
- td_values, 18

emissions_factors, 3

fuel_mix, 4, 6

generation_capacity, 5

get_fuel_mix, 6

get_fuel_mix(), 5

get_kaya_data, 7

get_kaya_data(), 11

get_top_down_trends, 8

get_top_down_trends(), 17

get_top_down_values, 9

get_top_down_values(), 18

kaya_data, 10

kaya_region_list, 11

kayadata (kayadata-package), 2

kayadata-package, 2

megawatts_per_quad, 11

plot_fuel_mix, 12

plot_kaya, 13

project_top_down, 15

regions, 4–6, 8–11, 16, 16, 17, 18

td_trends, 17

td_values, 18