

# Package ‘tidycorrgram’

June 15, 2026

**Type** Package

**Title** Tidy Correlation Matrices and 'ggplot2' Correlograms

**Version** 0.1.0

**Author** Xinyu Zhang [aut, cre]

**Maintainer** Xinyu Zhang <zhangx60@uci.edu>

**Description** Computes correlation matrices as tidy data frames and creates publication-ready correlograms with 'ggplot2'. The package is designed for teaching and exploratory analysis workflows where users want one consistent interface for selecting numeric variables, calculating pairwise correlations, optionally estimating p-values, reordering variables, and drawing tile, point, or mixed correlograms.

**License** MIT + file LICENSE

**Encoding** UTF-8

**RoxygenNote** 7.3.2

**Depends** R (>= 4.1.0)

**Imports** ggplot2, stats

**URL** <https://github.com/zhangx60/tidycorrgram>

**BugReports** <https://github.com/zhangx60/tidycorrgram/issues>

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2026-06-15 11:50:02 UTC

## Contents

tidycorrgram-package . . . . .	2
corrgram . . . . .	2
corrgram_data . . . . .	4
corrgram_palette . . . . .	5

<b>Index</b>	<b>6</b>
--------------	----------

---

tidycorrgram-package *Tidy Correlation Matrices and ggplot2 Correlograms*

---

## Description

Compute correlation matrices as tidy data frames and create publication-ready correlograms with **ggplot2**.

## Details

The main functions are [corrgram\\_data](#) for computing tidy correlation tables and [corrgram](#) for drawing correlograms.

## See Also

[corrgram\\_data](#), [corrgram](#)

---

corrgram *Create a correlogram*

---

## Description

`corrgram()` computes correlations and returns a **ggplot2** correlogram.

## Usage

```
corrgram(  
  data,  
  columns = NULL,  
  method = c("pearson", "kendall", "spearman"),  
  use = "pairwise.complete.obs",  
  triangle = c("lower", "full", "upper"),  
  diagonal = TRUE,  
  reorder = c("hclust", "none", "alphabetical"),  
  p_values = FALSE,  
  adjust = c("none", "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr"),  
  alpha = 0.05,  
  exact = NULL,  
  geom = c("tile", "point", "mixed"),  
  labels = FALSE,  
  label_digits = 2,  
  palette = corrgram_palette(),  
  significant_only = FALSE  
)
```

**Arguments**

<code>data</code>	A data frame.
<code>columns</code>	Optional column selection. Use <code>NULL</code> to select all numeric columns, a character vector of names, a numeric vector of positions, or a logical vector with length <code>ncol(data)</code> .
<code>method</code>	Correlation method passed to <code>stats::cor()</code> and <code>stats::cor.test()</code> .
<code>use</code>	Missing-value handling passed to <code>stats::cor()</code> .
<code>triangle</code>	Which part of the matrix to return: "full", "lower", or "upper".
<code>diagonal</code>	Should diagonal values be retained?
<code>reorder</code>	Variable ordering. "none" preserves the selected column order, "alphabetical" sorts names, and "hclust" uses hierarchical clustering on $1 - \text{abs}(\text{correlation})$ .
<code>p_values</code>	Should pairwise correlation p-values be computed?
<code>adjust</code>	P-value adjustment method passed to <code>stats::p.adjust()</code> .
<code>alpha</code>	Significance threshold used to create the significant column when <code>p_values = TRUE</code> .
<code>exact</code>	Passed to <code>stats::cor.test()</code> for rank-based methods. The default <code>NULL</code> lets R choose.
<code>geom</code>	Plot style. "tile" uses colored squares, "point" uses sized circles, and "mixed" combines both.
<code>labels</code>	Should correlation values be drawn as text?
<code>label_digits</code>	Number of digits for text labels.
<code>palette</code>	A named color vector with low, mid, and high values.
<code>significant_only</code>	If <code>TRUE</code> , non-significant off-diagonal cells are removed using adjusted p-values and alpha. This sets <code>p_values = TRUE</code> .

**Value**

A `ggplot2` object.

**See Also**

[corrgram\\_data](#), [corrgram\\_palette](#)

**Examples**

```
corrgram(mtcars, columns = c("mpg", "disp", "hp", "wt"))
corrgram(mtcars, geom = "point", triangle = "upper", diagonal = FALSE)
```

---

 corrgram\_data

*Compute a tidy correlation matrix*


---

### Description

corrgram\_data() selects numeric columns, computes pairwise correlations, and returns the matrix as a tidy data frame that is ready for **ggplot2**.

### Usage

```
corrgram_data(
  data,
  columns = NULL,
  method = c("pearson", "kendall", "spearman"),
  use = "pairwise.complete.obs",
  triangle = c("full", "lower", "upper"),
  diagonal = TRUE,
  reorder = c("none", "hclust", "alphabetical"),
  p_values = FALSE,
  adjust = c("none", "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr"),
  alpha = 0.05,
  exact = NULL
)
```

### Arguments

data	A data frame.
columns	Optional column selection. Use NULL to select all numeric columns, a character vector of names, a numeric vector of positions, or a logical vector with length ncol(data).
method	Correlation method passed to <code>stats::cor()</code> and <code>stats::cor.test()</code> .
use	Missing-value handling passed to <code>stats::cor()</code> .
triangle	Which part of the matrix to return: "full", "lower", or "upper".
diagonal	Should diagonal values be retained?
reorder	Variable ordering. "none" preserves the selected column order, "alphabetical" sorts names, and "hclust" uses hierarchical clustering on $1 - \text{abs}(\text{correlation})$ .
p_values	Should pairwise correlation p-values be computed?
adjust	P-value adjustment method passed to <code>stats::p.adjust()</code> .
alpha	Significance threshold used to create the significant column when p_values = TRUE.
exact	Passed to <code>stats::cor.test()</code> for rank-based methods. The default NULL lets R choose.

**Value**

A data frame with columns var1, var2, r, abs\_r, row, and col. If p\_values = TRUE, it also includes p, p\_adjusted, and significant.

**Examples**

```
corrgram_data(mtcars, columns = c("mpg", "disp", "hp", "wt"))  
corrgram_data(mtcars, triangle = "lower", diagonal = FALSE)
```

---

corrgram\_palette      *Create a diverging correlogram palette*

---

**Description**

Create a reusable three-color diverging palette for [corrgram](#).

**Usage**

```
corrgram_palette(low = "#3B4CC0", mid = "#F7F7F7", high = "#B40426")
```

**Arguments**

low	Color used for correlations near -1.
mid	Color used for correlations near 0.
high	Color used for correlations near 1.

**Value**

A named character vector with low, mid, and high.

**Examples**

```
corrgram_palette()  
corrgram_palette(low = "#2166AC", mid = "white", high = "#B2182B")
```

# Index

`corrgram`, [2](#), [2](#), [5](#)

`corrgram_data`, [2](#), [3](#), [4](#)

`corrgram_palette`, [3](#), [5](#)

`stats::cor()`, [3](#), [4](#)

`stats::cor.test()`, [3](#), [4](#)

`stats::p.adjust()`, [3](#), [4](#)

`tidycorrgram` (`tidycorrgram`-package), [2](#)

`tidycorrgram`-package, [2](#)